

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Assistant Commissioner for Patents
BOX PATENT APPLICATION
Washington, D. C. 20231

04/06/99
10553 U.S. PRO

I hereby certify that this correspondence is
being deposited with the United States Postal
Service as Express mail in an
envelope addressed to: Assistant Commissioner
of Patents, Washington, DC 20231.
Name: Gina M. Rossetto
DATE: 04/06/99 SIGNATURE: *Gina M. Rossetto*

10553 U.S. PRO
09/286723

04/06/99

Sir:

Transmitted herewith for filing is the patent application of
Inventor(s): Daniel C. Duggan
Entitled: RESTRAINT BRACKET FOR USE WITH CABLE TENSION

Enclosed are:

April 6, 1999

- ☒ 6 sheets of informal drawings (FIGS. 1-6)
- ☒ an abstract
- ☒ 21 pages of specification and claims
- ☒ 7 numbered claims
- ☒ Declaration
- ☒ verified statement(s) to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27.

The filing fee has been calculated as shown below:

| | Col. 1 No. Filed | Col. 2 No. Extra | Small Entity Rate Fee | Other than a Small Entity Rate Fee |
|---------------------------------------|---------------------|---------------------|---------------------------|---------------------------------------|
| Basic Fee | | | \$380.00 | \$760.00 |
| Total Claims | 7 -20 = | 0 | x \$9.00 = \$ | x \$18.00 = \$ |
| Independent Claims | 3 - 3 = | 0 | x \$39.00 = \$ | x \$78.00 = \$ |
| Multiple Dependent Claim Presented | | | + \$130.00 = \$ | + \$260.00 = \$ |
| | | | TOTAL DUE \$380.00 | |

- ☒ Please charge our Deposit Account No. 08-1388 in the amount of \$380.00.
- ☐ A duplicate copy of this sheet is enclosed.
- ☐ Our check No. _____ in the amount of \$ _____ to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication during the pendency of this application or credit any overpayment to Deposit Account No. 08-1388. A duplicate copy of this sheet is enclosed.
- ☒ Any additional filing fees required under 37 CFR 1.16.
- ☒ Any patent application processing fees under 37 CFR 1.17.
- ☐ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 08-1388. A duplicate copy of this sheet is enclosed.
- ☐ Any patent application processing fees under 37 CFR 1.17
- ☐ Any filing fees under 37 CFR 1.16 for presentation of extra claims.
- ☐ The issue fee set in 37 CFR 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR 1.311(b).

Respectfully submitted,

R. William Reinsmith
R. William Reinsmith
Registration No. 22,523
Murtha, Cullina, Richter and Pinney LLP
Attorneys for Applicant(s)

Enclosures

Our File: Loos Case 6

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Loos & Co., Inc.

Entitled: UNIVERSAL RESTRAINT CLIP FITTING

**VERIFIED DECLARATION CLAIMING SMALL ENTITY
STATUS [37 CFR 1.9(f) AND 1.27(b) - SMALL BUSINESS CONCERN]**

I hereby declare that I am:

- ☐ the owner of the small business concern identified below.
☒ an official of and empowered to act on behalf of the small business concern identified below:

NAME OF CONCERN: Loos & Co., Inc.

ADDRESS OF CONCERN: 901 Industrial Boulevard, Naples, FL 34104

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average, over the previous fiscal year of the concern, of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled UNIVERSAL RESTRAINT CLIP FITTING, invented by Daniel Duggan described in the specification filed herewith.

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who could not qualify as a small business concern under 37 CFR 1.9(d) or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

***NOTE:** Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27).

Name: N/A

Address: _____

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. [37 CFR 1.28(b)]

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified declaration is directed.

Name of Person Signing Anthony F. Naines

Title of Person President

Signature 

Address : 901 Industrial Boulevard, Naples, FL 34104

Date March 5, 1999

Attorney Docket: Loos Case 6

09286723-040699

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

Be it known that I, Daniel C. Duggan, citizen of the United States of America and residing in the City of St. Louis, County of St. Louis, State of Missouri, have invented certain new and useful improvements in a

RESTRAINT BRACKET FOR USE WITH CABLE TENSION BRACING

of which the following is a specification:

Our Ref: Loos Case 6

FIELD OF THE INVENTION

This invention relates to bracing of piping, ductwork and other structural features of buildings and is more particularly directed to apparatus intended primarily for use with tensioned cable sway control systems through use of a single configuration bracket which can be effectively and economically used with a variety of objects to be braced in a variety of cable systems, particularly those providing lateral, longitudinal and four-way sway bracing systems. The invention finds significant usage in bracing structural elements to control seismic induced object sway in earthquake conditions.

PRIOR ART

Because of the random occurrence of seismic shock waves (earthquakes) and the resulting high damage to property and life, Congress enacted Public Law 95-124 known as the Earthquake Hazards Reduction Act, which act has been amended and made the subject of presidential executive orders. A federal government interagency committee on seismic security in construction has been establishing standards not only for the retrofitting of existing buildings but also standards for new construction intended to reduce damage in the

event of an earthquake to the components of life safety systems such as sprinkler systems, electrical distributions systems, piping for various purposes and in general to develop seismic restraint requirements for use by architects, engineers and seismologists.

It has been determined that using cables in tension to dampen loads and to reduce sway of the object being stabilized, whether that device is piping, HVAC duct, ceiling grids, electrical conduit or other building elements, is more effective than use of compression braces which introduce radius of gyration limitations that reduce damping of loads and often lead to compression brace buckling failure.

Bracing techniques using cables are known and generally fall into either the 2-way brace to restrain object movement in a single direction or the 4-way brace to restrain both lateral and longitudinal object movement. Such techniques (whether 2-way or 4-way) generally comprise a plurality of cables of the appropriate length suitably affixed at one end to the support structure and the other end suitably affixed to the object to be restrained. Brackets have been devised for attachment to the cable ends to expedite connection of

the cable ends to a support surface and to the object. Conventional techniques for securing such brackets to the support surface have been used.

Whether working on new construction or retrofitting old construction, installers have generally been required to carry a wide variety of bracket configurations and sizes to accommodate the number of cables used to effect the desired type of bracing. Moreover, attempts to secure a plurality of brackets with a single fastener to the stabilized object or to the support surface have, on occasion, created excessive bending moments and loads upon the single fastener, often producing shear forces at the fastener.

OBJECTS OF THE INVENTION

It is a primary object of this invention to provide a universal restraint bracket having a structure and configuration that makes it suitable for simplified use in a cable tension system for dampening and sway reduction under seismic load conditions.

It is a further object of this invention to provide a restraint bracket or clip suitable for securement to a structural element such as a building wall or ceiling, to objects such as water pipes, electrical conduit, HVAC systems as well as their conventional supports and other apparatus used within the building to facilitate attachment of a cable system to dampen seismic shock induced apparatus sway.

It is an additional object of the invention to provide a restraint bracket for economical use in tensioned cable systems suitable for use with a single cable or a larger number of cables as the user may prefer.

It is yet another object of this invention to provide an easily manufactured universal restraint clip or bracket useable in the facile attachment of cables to a wide variety of objects, the clip being suitable for nesting to expand the cable attachment opportunities.

Other objects will be in part obvious and in part pointed out more in detail hereinafter.

SUMMARY OF THE INVENTION

The foregoing objects as well as other objects are achieved by this invention through utilization of a universal one piece restraint bracket which is particularly suited for use with wire rope seismic bracing systems. The universal bracket can be characterized as being generally L-shaped in top plan view to define a flattened apertured central portion with two wing portions arranged generally at right angles to each other and apertured at their free ends as well as being joined to the flattened central portion. Each such wing is upwardly bent away from the plane of the flattened central portion. The flattened centrally apertured portion can be affixed to either a supporting structure or to the device which is to be subjected to dampening forces in the event of forces such seismic loads; the brackets may be identical as the user may desire and can be sized depending upon the nature of the apparatus to be stabilized.

A better understanding of the objects, advantages, features, properties and relations of the invention will be obtained from the following detailed

description and accompanying drawings which set forth certain illustrative embodiments and are indicative of the various ways in which the principles of the invention are employed.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an elevational view showing a portion of a cable attached to a prior art bracket which bracket is centrally apertured to receive a threaded fastener and has an upwardly bent portion to receive a thimble and cable;

FIG. 1A is a top plan view of a prior art bracket, such as that shown in FIG. 1, without cable attachment;

FIG. 2 is a prior art illustration of typical HVAC duct in cross-section, partly broken away, showing lateral bracing;

FIG. 2A shows a top plan view of the HVAC duct of FIG. 2 with longitudinal and lateral sway protection typically provided by the prior art

using a single apertured bracket affixed to the mounting for the HVAC duct and with suitable cabling connected to walls, ceiling or the like (not shown);

FIG. 3 is a cross sectional view of an assembly, partly broken away, showing piping or conduit which may transmit water, gases or the like supported on a hanger and which are sway protected by cable devices extending from suitable prior art brackets engaging the hanger with cable extending to a stabilizing structure (not shown);

FIG. 3A is a top plan view of the assembly, partly broken away, of FIG. 3 wherein lateral and longitudinal sway protection is achieved by cables arranged in a general V shape and attached to a single bracket on each end of the hanger;

FIG. 3B is a top plan view of a prior art showing of a pair of single brackets in a stacked arrangement and which can be used in the assemblies of FIGS. 2, 2A, 3 and 3A.

FIG. 4 is a top plan view of a preferred embodiment of the universal restraint bracket of this invention generally illustrating its L-shaped configuration;

FIG. 5 is a perspective view of the bracket of FIG. 4 showing elevated wing portions of the bracket; and

FIG. 6 is a top plan view of two of the brackets of FIG. 4 in nested or stacked relation to one another.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT OF THE INVENTION

Before examining the details of the present invention, it is believed helpful to an understanding the present invention if the nature and status of typical prior art relating to shock bracing, particularly seismic shock bracing, are examined. Consideration of the prior art shown in the drawings is believed essential to an understanding of the problems solved by the present invention. Sway bracing systems to control object sway under, for example,

seismic shock conditions have resulted in the preferred prior art use of tensioned cable systems to provide lateral and longitudinal or four-way tensioned cable sway control. Certain fundamental cable concepts have been drawn from the prior art, particularly the marine field, and a fundamental unit is found in FIGS. 1 and 1A. Threaded fastener 10 extends through a suitable washer 11 and bracket 12 having an aperture 14. Bracket 12 may be secured to an object whose sway is to be controlled or to the support structure (not shown) by fastener 10. Cable 18 is of any suitable length and may have brackets such as at 12 at each cable end. Bracket 12 (see particularly FIG. 1A) is provided with an upwardly extending leg or wing 16 from a flat portion 17 of bracket 12. Wing 16 is provided with a suitable aperture 15 to accept cable 18 having a free end wrapped about a thimble 20 extending through aperture 15 with the cable end 22 being trained about thimble 20 and secured to the main cable portion by a suitable crimped fitting 24. This basic structure is a fundamental arrangement for tension sway bracing in the prior art.

Turning next to FIG. 2, it is seen that typical HVAC duct work 21 (shown in cross section) is supported by suitable rods 23 and 25 shown

within rod stiffeners 23A and 25A. The rods extend to and engage bottom object support 26, it being understood that rods 23,25 are fixed at their upper ends, not shown, to a support structure such as a building or structural element. A cable 28 of the type shown in FIG. 1 is attached to bottom support 26 by brackets 12 at each of its ends with opposite ends (not shown) of each cable 28,28 secured to the support structure. Such an arrangement is intended for transverse or lateral sway bracing by the cables under tension.

FIG. 2A shows a modified form of prior art sway bracing utilizing the bracket 12 of FIG. 1 wherein the duct work 23 (shown in top plan view) is supported as in FIG. 2 and is braced by two pairs of cables 29, 30 and 31, 32. Each cable pair 29, 30 and 31, 32 is secured to a wing 16 of its respective bracket 12. Such an arrangement provides both lateral and longitudinal bracing for object support member 26 and hence for the HVAC duct 23. Each cable extends through aperture 15 of its bracket 12 with a suitable thimble (not shown) and crimped fitting 24 provided as in FIG. 1.

Turning next to FIG. 3, there is seen a partial cross sectional view of a suitable hanger structure having rods 23 and 25 secured at upper ends to an

overhead support structure (not shown) and secured at their lower threaded ends by nuts such as at 27 to a support member 33 to which suitable U clamps 35 are secured to hold piping or electrical duct work 37 in position. Cable assemblies 38, 39 similar to those shown in FIGS. 1 and 2 are secured to opposite ends of the support member 33 through suitable brackets 12,12 to provide lateral sway bracing, the cables 38 and 39 being secured to a support structure, not shown, as desired.

FIG. 3A is a top plan view of an assembly slightly modified from that shown in FIG. 3 wherein conduit or the like 37 is supported on support member 33 by U clamps 35. The sway bracing is accomplished, however, by providing pairs of cables 40, 41 and 42, 43 which are each secured to support member 33 through a pair of apertured brackets 12 (with the usual thimble and fitting 24) and arranged such that the cables are secured to a support structure (not shown) to provide both horizontal and lateral sway protection because of the illustrated angular relationship of the cables.

In each of the foregoing prior art examples, a single clip or bracket 12 is utilized to affix a cable to the object to be braced. A single aperture is

provided in the bracket to accept one or more cable ends, and the resulting stresses imposed on brackets 12 by plural cable bracing techniques creates structural load points of reduced strength to resist the bracing loads, e.g., under a typical seismic sway load situation.

FIG. 3B shows a pair of single clips or brackets 12A,12B arranged with flat portion 17A of clip 12A overlying the corresponding flat portion 17B with their apertures (such as 14A) registering with one another. Legs 16A,16B of clips 12A,12B extend at a 90° angular displacement to one another. It is to be understood that the stacked double clip prior art arrangement of FIG. 3B is preferred to be substituted for the single clip shown in FIGS. 2,2A and 3,3A so as to have one clip for each cable end such as at 42,43 trained through each aperture 15A,15B. Forces applied upon loading of the cable such as at 42, for example, then minimize any tendency of the clip 12A to rotate about the bolt (not shown) extending through the registering apertures such as at 14A.

Turning now to the support bracket of this invention, it is seen in FIGS. 4 and 5 that a generally L shaped bracket 50 is provided, bracket 50 having a

central flat base or hub 52 and a pair of angularly disposed wings 54 and 56.

The central aperture 58 is provided for securing a bracket 50 to either a support structure or to the object to be sway braced, and suitable apertures 60 and 62 are provided in wings 54 and 56 for attachment of a cable and end fittings such as is used in the prior art.

It will be appreciated that there is only a single cable attached to each wing so as to better distribute the load and by virtue of the disclosed angular relationship of the wings 54,56, reduce stresses. As best seen in FIG. 5, wings 54 and 56 are upwardly bent away from the central flat portion or base 52 for optimal cable attachment. The bracket 50 is typically manufactured in bolt hole sizes to accommodate 1/4 inch through 1 1/4 inch bolts. The cable attachment wings 54,56 are normally capable of receiving size 12, size 18 or size 36 seismic wire rope/cable bracing. Moreover, to minimize undesired prying action of the bracket 50 when it is attached to a support structure and under stress, the cable apertures 60,62 are designed to be closer to the central bolt aperture 58 than in the prior art single clip.

565040" E292260

To provide the availability of a plurality of types of cable sway bracing (including lateral and longitudinal or four-way), an installer of sway bracing structure needs only a supply of brackets of this invention for attachment of cable earthquake sway bracing in multiple sway brace configurations without changing the bracket. The bracket shown in FIGS. 4 and 5 is constructed so that the main mounting hole 58 can be used with only a single sway bracing cable secured to the aperture 60 in its one wing 54 or, if desired and as seen in the drawings, wing 56 projects at about a 90° angle relative to wing 54 and is provided with an additional aperture 62 to accept an additional sway bracing cable. Thimbles and cables, with properly crimped fittings, are to be understood to be used to extend from the aperture 60 and 62 in each wing 54 and 56 to a support structure surface with but one cable preferably secured to each wing.

By forming brackets 50 of a material softer than the steel wire cable, the thimble may be dispensed with and an installer then may crimp an oval sleeve at any desired point along the cable. It will be appreciated by those skilled in the art that the universal restraint bracket of this invention is significantly lighter, smaller and less expensive to make than two single clips.

These advantages are further amplified by providing for easier field installation at either a support structure or suspended component. In addition, a single universal restraint bracket 50 is particularly convenient in certain applications using bolts, e.g., of a given length which are too short to accommodate double stacked single clip arrangements.

By virtue of the disclosed structure, multiple brackets of the type illustrated in FIGS. 4 and 5, because of the bracket heft, can be nested or stacked in offset relation (FIG. 6) to one another about their central aperture 58 for those situations when the sway bracing desired involves more than two cables. It is cautioned, however, that when the brackets are stacked to accommodate additional cable to be used in sway bracing, the fastener 10 must be adequate to resist the shear loads which will be applied. For example, two brackets 50,50A nested as shown in FIG. 6 can be stacked on hanger rods as clevis rings for attachment of four aircraft cables (not shown) as needed for 4-way earthquake sway brace assemblies. The universal restraint bracket or clip 50 of this invention accordingly can be used with two such brackets in stacked relation on a member to be braced by four cables

extending out from apertures 60,62 and 60A, 62A to structural members each using one such bracket 50 for the opposite end of each cable.

Although this invention has been illustrated and described with respect to an exemplary embodiment thereof, it should be understood by those skilled in the art that various changes, omissions and additions may be made without departing from the spirit and scope of the invention.

669040 "E2Z9B250

I claim:

1. A universal one piece restraint bracket in a wire rope sway bracing system for selective attachment to a structural element mounting surface and to a mounting surface of an object being braced to reduce sway damage and comprising

a planar apertured base intended to engage a mounting surface and to be secured thereto by a suitable fastening means extending through the apertured base;

a first wing member extending away from the apertured base at an angle to the plane of the apertured base, the first wing member being apertured to receive cable fastening means; and

a second wing member extending away from the apertured base at an angle to the plane of the apertured base, the second wing member being apertured to receive cable fastening means;

the apertured base, the first wing member and the second wing member being of unitary configuration.

2. The universal restraint bracket of claim 1 wherein each wing member extends at an angle of approximately 45° to the planar base.

3. The universal restraint bracket of claim 2 further including a second restraint bracket identical in configuration to the first restraint bracket, the second bracket being in nested relation to the first bracket, the first and second brackets having base apertures in aligned registration to be secured to the mounting surface by a common fastening means, the first wing member and second wing member of each bracket being disposed in spaced relation to the corresponding wing members of the other bracket to provide four apertured wing members in angularly spaced relation to one another about the base apertures of the brackets.

4. The universal restraint bracket of claim 1 wherein the bracket is formed of a material softer than the cable fastening means.

5. In a restraint apparatus for sway bracing of vertically supported water pipes, electrical conduit, electrical transformers and other objects subject to sway damage, a one piece restraint bracket comprising

a generally L shaped member having two wing portions extending away from a central portion, the central portion being flat and apertured to receive a mounting fastener for attachment to a mounting surface, the wing portions each being apertured adjacent their end and disposed generally in perpendicular relation to each other, each of the wing portions being bent upwardly from the central portion generally at a 45° angle.

6. The restraint apparatus of claim 5 including a plurality of restraint brackets, wherein the L shaped member of each bracket is attached by a mounting fastener extending through the apertured central portion to a mounting surface with the wing portions extending outwardly and away from the central portion, the wing portions each having apertures suitable for receiving an end of a cable having an opposite cable end affixed to a support.

7. A universal one piece restraint bracket in a wire rope bracing system for selective attachment to a mounting surface of a structural element and to a mounting surface of an object being braced to reduce sway damage and comprising

a centrally apertured washer-like flat hub, and

a pair of wings formed integrally with the hub and extending away from the hub, each the wings having its centerline intersecting with the center line of the other wing at a right angle at the central axis of the apertured hub, each wing being upwardly directed from a flat plane of the hub.

ABSTRACT

A universal one piece restraint bracket particularly suited for use with wire rope or cable for transverse, longitudinal and combined transverse and longitudinal seismic bracing systems for supporting an object. The bracket is generally L shaped to define a flattened apertured central portion with two wing portions generally at right angles to each other, apertured at their free ends and joined to the flattened central portion, each wing being elevated or upwardly bent away from the plane of the central portion. Aircraft type cables or wire rope connect the bracket to an adjacent support structure with the central portion of the bracket being secured to an object to be supported, whereby the bracing system acts in tension only so as to dampen earthquake loads and forces and thus is not subject to compression loads. A single bracket accommodates a wide variety of seismic bracing, and the bracket is configured for stacking with another bracket where necessary.





FIG. 1
PRIOR ART







FIG. 2A
PRIOR ART







FIG. 3A
PRIOR ART




FIG. 4




FIG. 5




FIG. 6

669040-EE298260

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name; that I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter claimed and for which a patent is sought in the application entitled:

UNIVERSAL RESTRAINT CLIP FITTING

which application is:

☒ [X] the attached application
(for original application)

☐ [] United States application Serial No. _____
or PCT International application . _____
filed _____ and amended on _____
(if applicable)
(for declaration not accompanying application)

that I have reviewed and understand the contents of the specification of the above-identified application, including the claims, as amended by any amendment referred to above; that I acknowledge my duty to disclose information of which I am aware and which is material to the patentability of this application under 37 C.F.R. 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code §119(a-d), §172 or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified on said list any foreign application for patent or inventor's certificate, or PCT International application on this invention having a filing date before that of the application on which priority is claimed:

| Application Number | Country | Filing Date | Priority Claimed |
|--------------------|---------|-------------|------------------|
| | | N/A | (yes or no) |

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below:

| Application Number | Filing Date |
|--------------------|-------------|
| | N/A |

I hereby claim the benefit of Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in a listed prior United States application or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge my duty to disclose any information material to the patentability of this application under 37 C.F.R. 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

| Application Serial No. | Filing Date | Status |
|------------------------|-------------|--------------------------------|
| | N/A | (patented, pending, abandoned) |

I hereby appoint Donald J. Hayes, Registration No. 19,021 and R. William Reinsmith, Registration No. 22,523, my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and request that all correspondence and telephone calls about the application be addressed to:

MURTHA, CULLINA, RICHTER AND PINNEY

CityPlace I - 30th Floor, 185 Asylum Street

Hartford, CT 06103-3469

Telephone Number (860) 240-6096

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Date 3/30/99

First Inventor Daniel Duggan
First Name Middle Initial Last Name

Residence 12049 Mereview Drive
St. Louis, MO 63146

Signature [Signature]

Post Office Address Loos & Co., Inc.
901 Industrial Boulevard, Naples, FL 34104

Citizenship United States of America

Date _____

Second Inventor _____
First Name Middle Initial Last Name

Residence _____

Signature _____

Post Office Address _____

Citizenship _____

1569040" E2798260